

SPECIFICATIONS

Customer Service: 1-800-460-7019

www.fluidfaucets.com

SOLUTIONS INTERNATIONAL

Specifications

- Heavy brass construction for durability and reliability
- High arc spout design with 360 degree rotation
- Kerox ceramic cartridge ensures life long trouble free service
- Single handle operation allows both volume and temperature control
- Quick and easy installation with top mounting system and quick hose connector
- Dual function brass spray head with spray and aerated flow
- Limited to flow rate of 1.5 gpm (5.7 lpm) at 60 psi
- Stainless steel flex supplies with 3/8" comp connection
- Max deck thickness 1-1/2"(38mm) w/ spacer and 2-1/8"(54mm) w/o
- Min 3-1/16"(78mm) distance from back splash wall
- 1-1/2" (38mm) single faucet hole drilling recommended
- 8" deck plate for 3 hole installation available and is sold separately

Finish


- CP (Polished Chrome)
- PVD-SS (PVD Stainless Steel)

Codes and Standards

- ANSI/ASME A112.18.1
- CSA B125.1
- NSF61-9
- ADA
- IAPMO / cUPC Listed
- AB1953 California Lead Plumbing Law Certified

Warranty

- Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.
- 2 Year Limited Warranty on all industrial, commercial and business applications.



fluid Palm Series **Pull Down Kitchen Faucet** Model: F823









