Fluid Innovative fixtures for life **SPECIFICATIONS**

Specifications

- Heavy brass construction for durability and reliability
- Tubular spout design with 360 degree rotation
- Kerox ceramic cartridge ensures life long trouble free service
- Single handle operation allows both volume and temperature control
- Quick and easy installation with top mounting system and quick hose connector
- Dual function spray head with spray and aerated flow
- Limited to flow rate of 1.5 gpm (5.7 lpm) at 60 psi
- Stainless steel flex supplies with 3/8" comp connection
- Max deck thickness 1-1/2"(38mm) w/ spacer and 2-1/8"(54mm) w/o spacer
- Min 3-1/8"(78mm) distance from back splash wall
- 1-1/2" (38mm) single faucet hole drilling recommended

Finish

- CP (Polished Chrome)
- PVD-SS (PVD Stainless Steel Finish)

Codes and Standards


- ANSI/ASME A112.18.1
- CSA B125.1
- NSF61-9
- ADA
- IAPMO / cUPC Listed (Pending)
- AB1953 California Lead Plumbing Law Certified (Pending)

Warranty

- Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.
- 2 Year Limited Warranty on all industrial, commercial and business applications.







SUSTAINABLE SOLUTIONS INTERNATIONAL